


**RIDGELINE™**
**FULL SYNTHETIC**
**GEAR OIL**
**SAE 75W-90**

### PRODUCT DESCRIPTION

RIDGELINE™ SAE 75W-90 FULL SYNTHETIC GEAR OIL is formulated to provide outstanding protection for hypoid gears, manual transmissions, gear boxes, passenger car and light truck conventional and limited slip differentials, transmissions, and steering gears. Recommended for use where an SAE 75W-90 gear oil that meets API Service GL-5 and MT-1, SAE J2360, and/or Mack GO-J is specified.

### APPLICATIONS

Hypoid gears, manual transmissions, gear boxes, passenger car and light truck conventional and limited slip differentials, transmissions and steering gears

### FEATURES AND BENEFITS

- Outstanding wear protection under extreme pressure and high torque operations.
- Immense resistance to thermal breakdown.
- Aid in the prevention of rust, corrosion, and foaming.
- Quieter, smoother operation.



Distributed by:  
**Parkland Corporation**  
 1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation

[www.ridgelinelubricants.ca](http://www.ridgelinelubricants.ca)  
[lubestechsupport@parkland.ca](mailto:lubestechsupport@parkland.ca)

## SPECIFICATIONS

RIDGELINE™ 75W-90 Gear Oil meets the requirements of the following engine specifications:

- AGMA 9005-E02, 250.03, 250.04, 251.02, No. 4
- AIST/US Steel 224
- API GL-5
- ArvinMeritor (Rockwell International) 076-E
- GM 9986115
- Limited Slip
- Mack GO-J, GO-H, GO-G
- MT-1
- SAE J2360, MIL-2105E/F

## TYPICAL PROPERTIES

Property	Test Method	75W-90
Gravity, °API	ASTM D287	32.52
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8627
Flash Point, °C	ASTM D92	232
Flash Point, °F	ASTM D92	450
Viscosity @ 40°C, cSt	ASTM D445	109.3
Viscosity @ 100°C, cSt	ASTM D445	16.15
Viscosity Index	ASTM D2270	159
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	135,000
Color	ASTM D1500	1

The physical property values above are typical of normal production and may vary.

## DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Parkland Fuel Corporation takes no responsibility for product misuse or misapplication.

Distributed by:  
**Parkland Corporation**  
**1800, 240 4 Ave SW, Calgary, AB T2P 4H4**

™ Trademark of Parkland Corporation

[www.ridgelinelubricants.ca](http://www.ridgelinelubricants.ca)  
[lubestechsupport@parkland.ca](mailto:lubestechsupport@parkland.ca)