

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4

1 Identification

Product Identifier: RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4
RL004K5G

Stock Number:

Other means of identification: No data available

Synonyms:

Recommended use and restrictions on use: Motor Oil

Recommended use: Uses other than those described above

Restrictions on use: Parkland Corporation

Initial Supplier Identifier: 1800, 240 4 Ave SW, Calgary, AB, T2P 4H4

Tel No.: +1-403-567-2500

Email: sds@wd-wpp.com

Emergency telephone number and any restrictions on the use of that number, if applicable: Monday-Friday 8:00am-4:30pm MST
+1-403-357-6400

2 Hazard identification

Classification of the hazardous product:
Not classified under GHS

Hazard statements: Not applicable

Other hazards known to the supplier with respect to the hazardous product:

Physical hazards not otherwise classified None known.

Health hazards not otherwise classified None known.

3 Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS registry number and any unique identifiers	Concentration
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	64742-65-0	0.1 - 1
Petroleum distillates, hydrotreated heavy paraffinic	No data available	64742-54-7	45 - 70

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supersedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

4 First-aid measures

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye contact:	Use eye wash to remove a chemical from the eye. Flush the affected eye for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if irritation persists.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
The most important symptoms and effects, whether acute or delayed:	None known.
An indication of immediate medical attention and special treatment needed, if necessary:	No additional first aid information available.

5 Fire-fighting measures

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Hazardous Combustion Products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide
Special protective equipment and precautions for firefighters:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:	No health effects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations
---	---

Safety Data Sheet



Stock Number: RL004K5G
 Date of the latest revision of the safety data sheet: 22-06-2020
 Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

found in Section 8 of this SDS.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7 Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure.
Conditions for safe storage: Store in a cool dry place. Isolate from incompatible materials.
Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents

8 Exposure controls/personal protection

Control parameters, including occupational exposure limit values or biological limit values and the source of those values:

Canada – Alberta – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Canada – British Columbia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	0.2 mg/m ³ TWA (mildly refined); 1 mg/m ³ TWA (severely refined)	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	No data available	No data available

Canada – Manitoba – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits -	Occupational Exposure Limits -	Occupational Exposure Limits -

Safety Data Sheet



Stock Number: RL004K5G
 Date of the latest revision of the safety data sheet: 22-06-2020
 Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

	TWAs	STELs	Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	No data available	No data available

Canada – New Brunswick – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Canada – Newfoundland & Labrador – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	No data available	No data available

Canada – Northwest Territories – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Canada – Nova Scotia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	No data available	No data available

Safety Data Sheet



Stock Number: RL004K5G
 Date of the latest revision of the safety data sheet: 22-06-2020
 Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Canada – Nunavut – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Canada – Ontario – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	No data available	No data available

Canada – Prince Edward Island – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	No data available	No data available

Canada – Quebec – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAEVs	Occupational Exposure Limits - STEVs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	No data available	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	No data available	No data available

Canada – Saskatchewan – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates,	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Safety Data Sheet



Stock Number: RL004K5G
 Date of the latest revision of the safety data sheet: 22-06-2020
 Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

hydrotreated heavy paraffinic			
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Canada - Yukon – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Chemical Name	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	IDLH
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Appropriate engineering controls: Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye and face protection: Wear safety glasses when handling this product if there is a likelihood of contact with eyes.

Skin Protection: Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Hand protection: Neoprene, Nitrile

General hygiene conditions: No data available

9 Physical and chemical properties

Physical state: Liquid
Colour: Amber

Safety Data Sheet



RIDGELINE

Stock Number: RL004K5G

Date of the latest revision of the safety data sheet: 22-06-2020

Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Odour:	Mild Petroleum
Odour threshold:	Not determined
pH:	No data available
Melting point (°C):	No data available
Freezing point (°C):	No data available
Initial boiling point and boiling range (°C):	No data available
Flash point (°C):	225
Evaporation rate:	No data available
Flammability, in the case of solids and gases:	No data available
Upper flammable or explosive limit, % in air:	Not established
Lower flammable or explosive limit, % in air:	Not established
Vapour pressure:	No data available
Vapour density:	No data available
Relative density:	0.85
Solubility:	Not determined
Partition coefficient — n-octanol/water:	No data available
Auto-ignition temperature (°C):	No data available
Decomposition temperature (°C):	Not determined
Viscosity:	82.93

10 Stability and reactivity

Reactivity:	There are no known reactivity hazards associated with this product.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid, including static discharge, shock or vibration:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Carbon monoxide Sulfur containing gases Nitrogen containing gases oxides of phosphorus Hydrogen sulfide

11 Toxicological information

Information on the likely routes of	Eye contact, Ingestion, Inhalation, Skin contact
--	--

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

exposure (inhalation, ingestion, skin and eye contact):

Symptoms related to the physical, chemical and toxicological characteristics: None known.

Immediate effects from short term exposure:

Inhalation: Likely to be practically non-toxic based on animal data. No hazard in normal industrial use.
Skin Contact: This material is likely to be slightly irritating to skin based on animal data. Can cause minor skin irritation, defatting, and dermatitis.
Eye Contact: This material is likely to be non-irritating to eyes based on animal data.
Ingestion: Estimated to be > 5.0 g/kg. No hazard in normal industrial use.

Delayed and chronic effects from long term exposure:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive and Developmental Toxicity: Not known or reported to cause reproductive or developmental toxicity.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.
STOT-single exposure: Based on available data, the classification criteria are not met.
STOT-repeated exposure: Based on available data, the classification criteria are not met.
Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity, including ATEs Based on available data, the classification criteria are not met.

12 Ecological information

Ecotoxicity (aquatic and terrestrial, if available): Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Ecological Toxicity Data:

Chemical Name	CAS registry number and any unique identifiers	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability: Biodegrades slowly.
Bioaccumulative potential: Bioconcentration may occur.
Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Other adverse effects: None known.

13 Disposal considerations

Information on safe handling for disposal and methods of disposal, including any contaminated packaging: Spent or discarded material is non-hazardous according to environmental regulations.

14 Transport information

Transportation of Dangerous Goods by land (TDG):

UN number: Not regulated for road transport
UN Proper shipping name: Not applicable
Transport hazard class(es): Not applicable
Packing group: Not applicable

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG
UN Proper shipping name: Not applicable
Transport hazard class(es): Not applicable
Packing group: Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA
UN Proper shipping name: Not applicable
Transport hazard class(es): Not applicable
Packing group: Not applicable

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Environmental hazards according to the International Maritime Dangerous Goods Code and the United Nations Model Regulations: No
Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78) and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)): No data available
Special precautions in connection with transport or conveyance either within or outside the premises: No data available

15 Regulatory information

Safety, health and environmental regulations, made within or outside Canada, specific to the product in question:

Canada - Domestic Substances List (DSL):

Chemical Name	CAS No	Canada - Domestic Substances List (DSL)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Yes
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	Yes

Canada - Non-Domestic Substances List (NDSL):

Chemical Name	CAS No	Canada - Non-Domestic Substances List (NDSL)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Canada - Controlled Drugs and Substances:

Safety Data Sheet



RIDGELINE

Stock Number: RL004K5G

Date of the latest revision of the safety data sheet: 22-06-2020

Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Chemical Name	CAS No	Schedule I	Schedule II	Schedule III	Schedule IV	Schedule V	Schedule VII	Schedule VIII
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No	No	No

Chemical Name	CAS No	Class A Precursors	Class B Precursors	Exempt Precursors	Class 1 Targeted Substances	Class 2 Targeted Substances
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No

Canada - CEPA - Schedule III Export Control List:

Chemical Name	CAS No	Part 1 Prohibited Substances	Part 2 Substances Subject to Notification or Consent	Part 3 Restricted Substances	Export Control List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No

Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting:

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Chemical Name	CAS No	Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Canada - Narcotic Control Regulations (C.R.C., c. 1041):

Chemical Name	CAS No	Canada - Narcotic Control Regulations (C.R.C., c. 1041)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Canada - Ontario - Toxics Reduction - List of Priority Toxics:

Chemical Name	CAS No	Canada - Ontario - Toxics Reduction - List of Priority Toxics
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Stockholm Convention on Persistent Organic Pollutants:

Chemical Name	CAS No	Stockholm Convention on Persistent Organic Pollutants
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:

Safety Data Sheet



Stock Number: RL004K5G
 Date of the latest revision of the safety data sheet: 22-06-2020
 Supercedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

Chemical Name	CAS No	Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade .
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs):

Chemical Name	CAS No	(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Montreal Protocol on Substances that Deplete the Ozone Layer:

Chemical Name	CAS No	Montreal Protocol on Substances that Deplete the Ozone Layer
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.:

Chemical Name	CAS No	Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No

16 Other information

Date of the latest revision of the safety 22-06-2020

Safety Data Sheet



Stock Number: RL004K5G
Date of the latest revision of the safety data sheet: 22-06-2020
Supersedes: 21-06-2020

RIDGELINE FULL SYNTHETIC SAE 0W-40 HEAVY DUTY ENGINE OIL CK-4 5GAL

data sheet:

Revision Number:

Reason for revision:

Disclaimer:

8

NEW VERSION

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.